

### Amendments to the Claims

1. (Currently Amended) ~~A sealing, trimming or guiding strip~~ An assembly for a window frame of a vehicle, said assembly comprising: ~~said strip being disposed to selectively contact a window pane having an interior side and an exterior side, said strip comprising:~~

a strip;

a window pane fixed in position relative to the strip and having an interior side for facing an interior of the vehicle and an exterior side for facing an exterior of the vehicle, and

the strip including a length of extruded material in contact with the exterior side of the window pane forming part of the strip, and a portion of the extruded material along only part of the length of the extruded material having been removed and replaced with molded material in contact with the interior side of the window pane and which is molded onto and thereby connected to the extruded material along only part of the length of the extruded material,

the extruded material including a channel for receiving a flange of the window frame and a rigid reinforcing carrier embedded within the extruded material in a region corresponding to the channel,

~~the channel remaining as part of the strip after removal of said portion of the extruded material,~~

the molded material forming a first window pane receiving surface at the interior side of the window pane,

the extruded material extending from the channel and having a second window pane receiving surface at the exterior side of the window pane and a generally oppositely facing surface facing opposite the second window pane receiving surface at the interior side of the window pane and directly visible from the exterior of the vehicle, this extended extruded material also remaining as part of the strip after removal of said portion of the extruded material, and

the molded material including at least one integral formation at the interior side of the window pane for securing the molded material to the window frame.

2. (Currently Amended) The assembly strip according to claim 1, wherein the molded material is extended to form a closed loop.

3. (Currently Amended) The assembly strip according to claim 2, wherein the length of extruded material beyond the portion thereof extends from the closed loop.

4. (Cancelled)

5. (Currently Amended) The assembly strip according to claim 1, wherein at least one of the integral formations comprises an aperture in the molded material through which a clamping member is disposed.

6. (Currently Amended) The assembly strip according to claim 5, wherein the clamping member is attached to the window pane and the window pane is secured to the window frame by the clamping member passing through the aperture in the molded material and through a further aperture in the window frame.

7. (Withdrawn - Currently Amended) The assembly strip according to claim 1, wherein at least one of the formations comprises a clamping member integrally formed with the molded material for cooperating with corresponding formations in the window frame.

8. (Withdrawn - Currently Amended) The assembly strip according to claim 1, wherein at least one of the formations comprises a clamping member embedded in the molded material for cooperating with corresponding formations in the window frame.

9. (Withdrawn - Currently Amended) The assembly strip ~~strip~~ according to claims 5, further comprising a rigid member embedded in the molded material and having an aperture therein through which the clamping member passes.
10. (Currently Amended) The assembly strip ~~strip~~ according to claim 1, wherein the extruded material includes a plurality of integral formations for securing the extruded part to the window frame.
11. (Currently Amended) The assembly strip ~~strip~~ according to claim 1, further comprising an elongate rigid member into which a portion of the strip is fitted.
12. (Currently Amended) The assembly strip ~~strip~~ according to claim 11, wherein the molded material is fitted into the rigid member so as to clamp the window pane fitted in said molded material.
13. (Currently Amended) The assembly strip ~~strip~~ according to claim 11, wherein the rigid member also accommodates a further length of extruded material having a window pane receiving channel.
14. (Currently Amended) The assembly strip ~~strip~~ according to claim 11, wherein the rigid member is of substantially H shape.
15. (Withdrawn - Currently Amended) The assembly strip ~~strip~~ according to claim 8, wherein the embedded clamping member includes a rigid base portion extending towards the channel so as to increase the force required to remove the strip from the window frame.

16. (Withdrawn - Currently Amended) The assembly strip according to claim 9, wherein the embedded rigid member extends towards the channel so as to increase the force required to remove the strip from the window frame.

17. (Currently Amended) The assembly strip according to claim 1, wherein the extruded material includes a limb forming at least a part of a window pane receiving channel,~~a portion of the window pane receiving channel being removed by removal of said portion of the extruded material.~~

18. (Currently Amended) A method of forming a ~~sealing, trimming or guiding~~ strip for a window frame comprising a flange and a window pane having an interior side and an exterior side, the method including:

extruding a length of material to form part of the strip,

removing a portion of the extruded material along part only of the length thereof,  
[[and]]

replacing the [[said]] portion with molded material which is molded onto and thereby connected to the extruded material; and

assembling the strip to the window pane so that the window pane is fixed in position relative to the strip; wherein:

the extruded material includes a channel for receiving the flange of the window frame and a rigid reinforcing carrier embedded within the extruded material in a region corresponding to the channel,

the channel remains as part of the strip after removal of said portion of the extruded material,

the molded material forms a first window pane receiving surface at the interior side of the window pane,

the extruded material extends from the channel and has a second window pane receiving surface at the exterior side of the window pane and a generally oppositely facing surface for disposition at the interior side of the window pane ~~directly visible from the exterior of the vehicle~~, this extended extruded material also remaining as part of the strip after removal of said portion of the extruded material; and

the molded material includes at least one integral formation for securing the molded material to the window frame.

19. (Original) The method according to claim 18, wherein the molded material is extended to form a closed loop.

20. (Previously Presented) The method according to claim 19, wherein the length of extruded material beyond the said portion thereof extends from the closed loop.

21. (Cancelled)

22. (Previously Presented) The method according to claim 18, wherein at least one of the integral formations comprises an aperture in the molded material through which a clamping member passes.

23. (Previously Presented) The method according to claim 22, wherein the clamping member is attached to the window pane and the window pane is secured to the window frame by the passage of the clamping member through the aperture in the molded material and through a further aperture in the window frame.

24. (Withdrawn) The method according to claim 18, wherein at least one of the formations comprises a clamping member integrally formed with the molded material for cooperating with corresponding formations in the window frame.

25. (Withdrawn) The method according to claim 18, wherein at least one of the formations comprises a clamping member embedded in the material for cooperating with corresponding formations in the window frame.

26. (Withdrawn) The method according to claims 22, wherein a rigid member is embedded in the molded material and has an aperture therein through which the clamping member passes.

27. (Original) The method according to claims 18, wherein the extruded material includes a plurality of integral formations for securing the extruded part to the window frame.
28. (Original) The method according to claim 18, including a step of providing an elongate rigid member into which a portion of the strip is fitted.
29. (Previously Presented) The method according to claim 28, wherein the molded material is fitted into the rigid member so as to clamp the window pane fitted in said molded material.
30. (Original) The method according to claim 28, wherein the rigid member also accommodates a further length of extruded material having a third window pane receiving channel.
31. (Original) The method according to claim 28, wherein the rigid member is of substantially H shape.
32. (Withdrawn) The method according to claim 25, wherein the embedded clamping member includes a rigid base portion extending towards the channel so as to increase the force required to remove the strip from the window frame.
33. (Withdrawn) The method according to claim 26, wherein the embedded rigid member extends towards the channel so as to increase the force required to remove the strip from the window frame.

34. (Original) The method according to claims 18, in which the extruded material is provided with a limb forming at least a part of a window pane receiving channel, a portion of the window pane receiving channel being removed by removal of said portion of the extruded material.

35. (Withdrawn) The method according to claim 34, in which the limb has an embedded rigid member therein for reducing the tendency for the limb to bend as it emerges from an extruder device used to form the strip.

36. (Withdrawn) The strip according to claim 17, wherein the limb has an embedded rigid member therein for reducing the tendency for the limb to bend as it emerges from an extruder device used to form the strip.

37. (Withdrawn) A sealing, trimming or guiding strip for a window frame of a vehicle, comprising

a length of extruded material extending along and forming part of the strip,

wherein the extruded material comprises a limb forming at least part of a glass pane receiving channel, and which limb has an embedded rigid member therein for reducing the tendency of the limb to bend as it emerges from an extruder device used to form the strip.

38. (Previously Presented) The strip according to claim 1, wherein the oppositely facing surface is at the interior side of the window pane with the window pane disposed between the second window pane receiving surface and the oppositely facing surface.